

Akamai's V6 Rollout Plan and Experience from a CDN Point of View

Christian Kaufmann Senior Manager Network Architecture Akamai Technologies, Inc.

Agenda




- About Akamai
- General IPv6 transition technologies
- Challenges of reaching IPv6 users via transition technologies
- Challenges of reaching IPv6 users natively
- Akamai's IPv6 development
 - Engineering: Mapping, EdgePlatform, Back End, etc.
 - Network
- Akamai's IPv6 Transition Phases
 - Early Adoption Phase
 - End User Transition Phase
 - Origin Transition Phase
- Current status
- Experience with IPv6
 - DNS / Mapping
 - Server OS
 - Network
 - IP allocation



The Akamai System

The world's largest on-demand, distributed computing platform delivers all forms of Web content and applications for over 3,400 customers and 20,000 domains

The Akamai EdgePlatform:





General IPv6 transition technologies

Tunneling

- encapsulates IPv6 packets inside of IPv4 packets
- Tunneling is used to connect v6 islands with no connectivity together
- Can cause performance and reliability issues
- CGN/NAT64
 - NAT64 provides connectivity between IPv6 hosts and IPv4 hosts by translating between IPv6 and IPv4 packet streams
 - Might cause performance issues or be a single point of failure
- Dual Stack
 - running both the IPv4 and IPv6 protocol stacks at the same machine
 - Must be supported by hard- and software
 - Requires enough IPv4 address space for all dual-stacked devices
- Each transition technology has its limitations and drawbacks, but they are necessary until the long IPv6 migration is complete.



Challenges of reaching IPv6 users via transition technologies

- Broken location-aware services
 - Caused by CGN's and Tunneling
 - Licensing content under geographic restrictions
 - *abuse mitigation*—IP blacklisting or whitelisting
 - Web site analytics relying on geo-location

Broken applications

- VoIP
- Peer to Peer traffic
- Complex troubleshooting
- Poor performance
 - Because of limited CGN deployments (latency, congestions)
 - Because of tunneling (MTU, latency)
- Worst case scenario, multiple NAT and CGN in a row



Challenges of reaching IPv6 users natively

- Delivering IPv6 natively during the transition phase will face several key challenges:
 - Often lower performance, because of less direct routes and tunnels
 - Reliability issues, because of fewer network interconnections and less monitoring
 - Denial-of-service because of browser and OS bugs, broken home gateways
 V6 end-user asks for a AAAA but has no working v6 connectivity
 - Whitelists create management and scalability challenges Restricting AAAA responses can cause issues, as there is no direct correlation between DNS IPv6 support and end user IPv6 connectivity.
 - Lack of IPv6 reporting and analytics
 - IPv6 "support" often does not mean performance parity with IPv4



Challenges of reaching IPv6 users natively – Performance Examples

- A test with more than 9k name servers worldwide showed:
 - For North America tests showed a median IPv4 latency of 48 ms compared to a median IPv6 latency of 87 ms
 - For tunneled IPv6 traffic, the difference in latencies was even more significant
- Download tests from <u>www.akamai.com</u> showed similar results:
 - The median speed via IPv4, was almost 2x faster than via IPv6.
 - Of the 4000+ clients who were able to reach us via IPv6 in this test:
 - only 10.6% of them had a native IPv6 addresses
 - the rest came over tunnels.

Akamai IPv6 Engineering: Mapping, EdgePlatform, Back End, etc.

- Native IPv6 Support in the EdgePlatform Servers and throughout the system
 - Including for example log files for our customer
- Mapping the IPv6 Internet
 - Significant effort in making the mapping system v6 capable
 - The evolving topology of the IPv6 Internet required iterative surveying and mapping efforts
- Understanding the performance differences between IPv4 and IPv6
 - Real-time mapping topology for IPv6 is independent of IPv4
 - End-user will get the content via v4 or v6 depending on which protocol has a better performance
- Making the IPv6 Internet Reliable

Akamai's IPv6 development: Network



- ALPIX, Equinix Ashburn, Equinix Singapore, FranceIX, NLIX, INEX, NAMEX, SIX, INXS, DECIX
- The rest till end of Q1
- Requesting IPv6 blocks from all network partners
 - Already started

nai




Akamai's IPv6 Early Adoption Phase

- Early Adoption Phase Q1 2011
 - Selected set of customer
 - IPv6 only site and/or beacon
 - Customers who are interested in joining should contact us.
- Akamai will enable early adopters to offer IPv6 content through a separate hostname, without changing their IPv4 networking infrastructure and without affecting existing users.
 - For example: <u>http://ipv6.akamai.com</u>
 - This allows customers to ensure that client IPv6 addresses work end-to-end: in their reporting, IDS, log processing, etc.
 - prior to enabling it for their full production site, but without needing IPv6 connectivity at the network level.
- Customers can offer their services on IPv6 immediately
 - Without spending time or money on training, software, hardware, etc.
 - For what is currently a small percentage of the user base
 - Gives customer time to build up expertise on IPv6 in a controlled manner

Akamai's IPv6 Early Adoption Phase








Akamai's IPv6 End User Transition Phase

- We anticipate having Beta service available in 2H 2011, with Limited Availability in 1H 2012.
- Customers will be able to deliver optimized experiences to all of their users across the hybrid Internet on a single hostname, without changing their IPv4 network infrastructure.
- Avoid CGN, tunnels, indirect routes, and other performance and reliability bottlenecks

• Example:

- Dual stacked user makes a request to a customer site
- Mapping system will determine if the user can be served via IPv6 or via IPv4
- IPv6: User will receive an IPv6 or an IPv4 address of an optimal server
- IPv4: Only an IPv4 addresses will be returned
- customer can choose how aggressively they prefer v6 over v4

Akamai's IPv6 End User Transition Phase



State of The Internet Report


Akamai's IPv6 Origin Transition Phase



- Akamai will support dual stack or IPv6 only origin infrastructures • so that customers may transition their origin infrastructures when they are ready to.
- Provide seamless origin server transition to IPv6—no impact to ۲ end users



Akamai's IPv6 Origin Transition Phase Galamai





Current status



- Akamai is already delivering IPv6 traffic out of some clusters for testing purposes
 - deployment is limited but growing
 - Some advanced features are not ready yet
- IPv6 beacon on <u>www.akamai.com</u> to check for IPv6 capable end-users
- Supporting ISOC's IPv6 day for selective customer wishing to participate.



• Handling an "IP" in our software as an abstraction

- rather than have separate data types or separate fields for IPv4 vs IPv6).
- This is more work up-front, but it often ends up being cleaner in the end.
- Still finding v6 bugs in Client-OS but not yet on our underlying Linux Server OS.

Experience with IPv6 – Network



Router OS

- No big problem with current OS version
- Configurations
 - Standard configurations
 - A lot of examples and best practices are online available

Network Interconnects

- Still not every transit provider can offer v6 in every pop.
- Present at 46 IX in the world with thousands of sessions, a lot of admin / manual work to get the same connectivity like in v4.



Experience with IPv6 – IP allocation

• ARIN space:

- 2600:1400::/27
- Multiple discrete network policy
- Announcing a /32 per peering or transit cluster
- RIPE space
 - 2a02:26f0::/32
 - Announcing a /48 per peering or transit cluster
- This will have an impact on the v6 routing table size
- Using a /64 /48 per on-net deployment from the partner network



- Credits: David Belson, Erik Nygren, Matthew Levine
- URL: <u>http://www.akamai.com/ipv6</u>
- Questions:

ck@akamai.com